



SUGGESTED PANEL CUTOUT



SCHEMATIC



SPECIFICATIONS

**FUNCTION:**  
 2P1T OFF-ON  
 Auto OFF Below Calibration Voltage  
 Remote Trip

**RATINGS:**  
 ANSI/UL 508 and CAN/CSA C22.2 No.14 (E195908):  
 16A 220-240VAC [cURus]  
 2HP 220-240VAC (12A FLA, 72A LRA) [cURus]

**CALIBRATION VOLTAGE:**  
 Use: 230V 60Hz  
 Release: 120-160V

**ELECTRICAL LIFE:**  
 6,000 Cycles [cURus]

**INGRESS PROTECTION:**  
 IP55

APPROVALS:



COLORS AND MARKINGS

**BEZEL:**  
 Black

**ACTUATOR:**  
 ON: Green  
 OFF: Red

**MARKING:**  
 I/O Vertical (1)

**MARKING COLOR:**  
 White

MATERIALS

**UPPER BODY:**  
 Polyamide 6/6 (PA66)

**LOWER BODY:**  
 Polyamide 6/6 (PA66+G10)

**BEZEL:**  
 Polyamide 6/6 (PA66+G10)

**ACTUATORS:**  
 Polyamide 6/6 (PA66)

**MOUNTING EARS:**  
 Polyamide 6/6 (PA66)

**COVER:**  
 Polyvinyl Chloride (PVC)

**CONTACTS:**  
 Silver Alloy Clad Copper (AgSnO/Cu)

**TERMINALS:**  
 Brass

**GASKET:**  
 Rubber

BODY	A	09/08/07	CAB
COLORS	A	09/08/07	CAB
MATERIALS	A	09/08/07	CAB
SPECIFICATIONS	A	09/08/07	CAB
REFERENCE	REV.	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED.

INITIAL RELEASE	22034	10/28/2015	MW
DESCRIPTION	PCR	DATE	DRAWN BY

DIMENSIONS	INCHES [MILLIMETERS]
GENERAL TOLERANCES	±0.020 [±0.5] / ±1"
SCALE	DRAWING NOT TO SCALE

KJD17-22413-112	
ITEM NUMBER	34-KJD1722413112
DATE	10/28/2015
REVISION	A