


SUGGESTED PANEL CUTOUT  
PANEL THICKNESS 0.6-8.0 [0.024-.315 in]

∅23.80  
[.937 in]

▲ GRAPHIC COLOR:  
WHITE



SWITCH FUNCTION	
POS. 1	POS. 3
OFF	ON
OPEN	1-2

▲ ACTUATOR COLOR:  
BLACK  
HOLD COLOR:  
BLACK

POS.

6.3±.5  
[.25±.02 in]

**OBSOLETE**  
**PCR 23059**  
**OCT. 2017**

21.8  
[.86±.02 in]

11.5  
[.46 in]

1.20  
[.047 in]

13.80  
[.543 in]

20.90  
[.823 in]

4.70  
[.185 in]

▲ ∅2.10  
[.083 in]

.80  
[.031 in]

7.10  
[.280 in]

NOTE:

- DIMENSIONS IN MM [INCH]
- GENERAL TOLERANCE: X.X = ± 0.4  
X.XX = ± 0.25
- TERMINAL NUMBERS FOR REF ONLY
- CONTACT RATING: 16A 125VAC [UL, cUL]  
10A 250VAC [UL, cUL]  
1/3HP 125/250VAC [UL, cUL]  
10(4)A 250V~ 1E4 T125/55 [SEMKO, ENEC]
- CONTACT RESISTANCE: 35mΩ MAX. @ 50VAC
- INSULATION RESISTANCE: 100MΩ MIN. @ 500VAC
- DIELECTRIC STRENGTH: 1,500VAC FOR 1 MINUTE
- ELECTRICAL LIFE: 10,000 CYCLES
- OPERATING TEMPERATURE: -20°C TO 105°C [UL, cUL]  
-20°C TO 125°C [SEMKO, ENEC]
- ▲ DENOTES CRITICAL PARAMETER
- 2011/65/EU (ROHS) COMPLIANT



A	23054	NEW RELEASE	10/20/17	MJR
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE RRG81C1121				
SCALE	DATE	DR	DWG	REV
3:2	10/20/2017	MJR	38-RRG81C1121	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED