


**SCHEMATIC**



**SPECIFICATIONS**

**FUNCTION:**  
1P1T OFF-ON

**RATINGS:**  
ANSI/UL 1054 and CAN/CSA C22.2 No. 55 (E194579):  
15A 125VAC T105 [cURus]

EN 61058-1:2002 and A2 (40018527):  
10(4)A 250V~ 1E4 T85/55 [ENEC10, VDE]

NOM-003-SCFI-2000 (200401C08000):  
15A 125VAC [NOM]

**ILLUMINATION VOLTAGE:**  
125V

**CONTACT RESISTANCE:**  
Initial: 20mΩ Max. at 1A 5VDC



**INSULATION RESISTANCE:**  
100MΩ Min. at 500VDC

**Dielectric Strength:**  
1,000VAC for 1 Minute

**ELECTRICAL LIFE:**  
6,000 Cycles [cURus]  
10,000 Cycles [ENEC10, VDE]

**TEMPERATURE:**  
Operating: -20°C to 105°C [cURus]  
Operating: -20°C to 125°C [ENEC10, VDE]

**APPROVALS:**



**OBSOLETE**  
 January 2018  
 PCR 23169

**COLORS AND MARKINGS**

**BODY:**  
Black

**ACTUATOR:**  
Transparent Red

**MARKINGS:**  
None

**MARKING COLOR:**  
None

**MATERIALS**

**BODY:**  
Polyamide 6/6 (PA66), UL94 V-2

**ACTUATOR:**  
Polycarbonate (PC), UL94 V-2

**LAMP CARRIER:**  
Polyamide 6/6 (PA66), UL94 V-2


**LAMP:**  
Neon Bulb

**SPRING:**  
Steel

**CONTACTS:**  
Silver Clad Copper

**TERMINALS:**  
Silver Plated Copper  
Silver Plated Brass  
Brass

**SUGGESTED PANEL CUTOUT**



ACTUATOR	A	09/08/19	CAB
BODY	A	09/08/19	CAB
COLORS	A	09/08/19	CAB
MATERIALS	A	09/08/19	CAB
SPECIFICATIONS	A	09/08/19	CAB
REFERENCE	REV.	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

INITIAL RELEASE	21408	3/17/14	ERP
DESCRIPTION	PCR	DATE	DRAWN BY

DIMENSIONS	
INCHES [MILLIMETERS]	
GENERAL TOLERANCES	
±0.008 [±0.2] / ±1°	
SCALE	PROJECTION
DRAWING NOT TO SCALE	1st Angle

<b>RSC141C1000-116</b>			
ITEM NUMBER	DATE	REVISION	
38-RSC141C1000116	MARCH 17, 2014	A	