



SPECIFICATIONS

FUNCTION: 1P1T OFF-ON

RATINGS:
 20A 125VAC T105 [UR, CLR]
 3/4HP 125VAC [UR, CLR]
 16(4)A 250V~ IE4 T85 [VD]
 ILLUMINATION VOLTAGE:
 125V

CONTACT RESISTANCE:
 Initial: 20mΩ Max. at 1A 5VDC

INSULATION RESISTANCE:
 100MΩ Min. at 500VDC

DIELECTRIC STRENGTH:
 1500VAC For 1 minute

ELECTRICAL LIFE:
 6,000 Cycles [UR, CLR]
 10,000 Cycles [VD]

TEMPERATURE:
 -20°C to 105°C [UR, CLR]
 -20°C to 85°C [VD]

APPROVALS:

COLORS AND MARKING

BODY:
 Black

ACTUATOR:
 Transparent Amber

MARKING:
 None

MARKING COLOR:
 None

MATERIALS

BODY:
 Polyamide 6/6 (PA66), UL94 V-2

ACTUATOR:
 Polycarbonate (PC), UL94 V-2

LAMP:
 Neon Bulb

SPRING:
 Piano Wire

CONTACTS:
 Silver Gild Copper

TERMINALS:
 Silver Plated Copper
 Silver Plated Brass

E SWITCH

LAMB INDUSTRIES

INCHES [MILLIMETERS]

GENERAL TOLERANCES ±0.008 [±0.2] / ±1'

SCALE DRAWING NOT TO SCALE

PROJECTION DRAWING NUMBER 38-RSCF241D1000126

DATE 05/11/12

REVISION A

ACTUATOR	REV.	DATE	BY
A	09/08/19	CAB	
BODY	A	09/08/19	CAB
COLORS	A	09/08/19	CAB
MATERIALS	A	09/08/19	CAB
SPECIFICATIONS	A	09/08/19	CAB
REFERENCE	REV.	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED

INITIAL RELEASE DESCRIPTION	FOR	DATE	DRAWN BY
	20261	05/11/12	TC