


ALL TERMINALS TO BE COPLANER WITHIN 0.1mm(0.004")



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X = ±0.4
X.XX = ±0.25
 3. RATING: 12VDC @ 50mA
 4. CONTACT RESISTANCE: 100mΩ MAX.
 5. INSULATION RESISTANCE: 100MΩ MIN.
 6. OPERATING FORCE: 160 ± 50gf
 7. TRAVEL: 0.2 ± 0.1mm
 8. OPERATING TEMPERATURE: -40°C to 85°C
 9. OPERATING LIFE 500,000 CYCLES
 - ▲ 10. LED COLOR: BLUE
 11. ▲ DENOTED CRITICAL PARAMETER
 12. 2011/65/EU (ROHS) COMPLIANT
 13. PACKAGE: 450 PIECES PER REEL.
 14. PART TO BE HALOGEN FREE.

| LED SPECS | UNITS | BLUE |
|--------------------|-------|---------------------|
| FORWARD CURRENT | mA | 20 |
| FORWARD VOLTAGE | V | 2.9 TYP. - 4.0 MAX. |
| LUMINOUS INTENSITY | MCD | 150 TYP. |



| | | | | |
|-----|--------|---------------------|---------|----|
| B | 23036 | update Package Note | 10/9/17 | MW |
| A | 22935 | New Release | 7/20/17 | rc |
| REV | PCR NO | DESCRIPTION | DATE | BY |

| | | | | |
|------------------|----------|----|---------|-----|
| TITLE TL3265BQNN | | | | |
| SCALE | DATE | DR | DWG | REV |
| 4:1 | 7/5/2017 | rc | B200070 | B |

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED