


ALL TERMINALS TO BE COPLANAR WITHIN 0.1mm(0.004")



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: X.X = ±0.4  
X.XX = ±0.25
  3. RATING: 12VDC @ 50mA
  4. CONTACT RESISTANCE: 100mΩ MAX.
  5. INSULATION RESISTANCE: 100MΩ MIN.
  6. OPERATING FORCE: 160 ± 50gf
  7. TRAVEL: 0.2 ± 0.1mm
  8. OPERATING TEMPERATURE: -40°C to 85°C
  9. OPERATING LIFE 500,000 CYCLES
  - ▲ 10. LED COLOR: RED
  11. ▲ DENOTED CRITICAL PARAMETER
  12. 2011/65/EU (ROHS) COMPLIANT
  13. PACKAGE: 450 PIECES PER REEL.
  14. PART TO BE HALOGEN FREE.

LED SPECS	UNITS	RED
FORWARD CURRENT	mA	20
FORWARD VOLTAGE	V	1.95 TYP. - 2.5 MAX.
LUMINOUS INTENSITY	MCD	1800 TYP.



B	23036	update Package Note	10/9/17	MW
A	22935	New Release	7/21/17	rc
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE TL3265RQNN				
SCALE	DATE	DR	DWG	REV
4:1	7/5/2017	rc	B200072	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED