



ALL TERMINALS TO BE
COPLANER WITHIN
0.1mm(0.004")

- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X = ±0.4
X.XX = ±0.25
 3. RATING: 12VDC @ 50mA
 4. CONTACT RESISTANCE: 100mΩ MAX.
 5. INSULATION RESISTANCE: 100MΩ MIN.
 6. OPERATING FORCE: 160± 50gf
 7. TRAVEL: 0.2± 0.1mm
 8. OPERATING TEMPERATURE: -40°C to 85°C
 9. OPERATING LIFE 500,000 CYCLES
 - ▲ 10. LED COLOR: GREEN
 11. ▲ DENOTED CRITICAL PARAMETER
 12. 2011/65/EU (ROHS) COMPLIANT
 13. PACKAGE: SWITCHES ARE 450 PIECES PER REEL
BUTTONS WILL BE BAGGED SEPERATELY
450 BUTTONS PER BAG
 14. PART TO BE HALOGEN FREE.
 15. BUTTONS TO BE ASSEMBLED ONTO THE SWITCH AFTER SOLDERING.

LED SPECS	UNITS	GREEN
FORWARD CURRENT	mA	20
FORWARD VOLTAGE	V	2.1 TYP. - 2.5 MAX.
LUMINOUS INTENSITY	MCD	800 TYP.

B	23036	update Package Note	10/9/17	MW
A	22935	New Release	7/20/17	rc
REV	PCR NO	DESCRIPTION	DATE	BY

E-SWITCH®

TITLE TL3265GQTCLR

SCALE 4:1	DATE 7/5/2017	DR rc	DWG B200077	REV B
-----------	---------------	-------	-------------	-------

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED