



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: x.x=±0.4mm  
x.xx=±0.25mm
  3. RATING: DC 30V, 0.3A
  4. OPERATING FORCE: 200±100gf
  5. TRAVEL: 3.3mm FULL TRAVEL  
2.5mm TO LOCK
  6. LIFE CYCLES: 10,000 CYCLES
  7. OPERATING TEMPERATURE: -20°C TO 70°C
  8. CONTACT RESISTANCE: 20mΩ MAX.
  9. INSULATION RESISTANCE: 100MΩ MIN@ 500VDC.
  - ▲10. LED COLOR: BICOLOR GREEN-BLUE
  11. ▲ DENOTES CRITICAL PARAMETER.
  12. 2002/95/EC (RoHS) COMPLIANT.

LED SPECS	UNITS	GREEN	BLUE
FORWARD CURRENT	mA	20	20
FORWARD VOLTAGE @20mA	V	1.7 Typ-2.6 Max	3.3 Typ - 4.0 Max
LUMINOUS INTENSITY @ 10mA	MCD	4.7-7.8	60 Typ



A	20704	New-Release	8/13/12	rc
REV	PCR NO	DESCRIPTION	DATE	BY
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED				

TITLE WBL4UEEGBQ				
SCALE	DATE	DR	DWG	REV
2	8/13/2012	rc	B400013	A