



- NOTE:**
1. ALL DIMENSIONS IN MM[INCH].
 2. GENERAL TOLERANCE: X.X ± 0.4
X.XX ± 0.25
 3. TERM. NUMBERS FOR REFERENCE ONLY.
 4. CONTACT MATERIAL: SILVER
 5. CONTACT RATING: 125VAC 0.3A
 6. OPERATING FORCE 425 ± 100CM/STANDARD
 7. OPERATING TEMP: -30°C to 85°C
 - ▲ 8. CIRCUIT SP: 3 POSITION 30° INDEX.
 9. DIELECTRIC STRENGTH: 1000V RMS MIN. @ SEA LEVEL
 - ▲ 10. HARDWARE SUPPLIED ON SWITCH: LOCKWASHER, HEXNUT, STOP RING
 11. ▲ DENOTES CRITICAL PARAMETER.



B	24068	update drawing, correct note 5	10/16/19	MW
A	16188	NEW PART RELEASE	6/28/06	CT
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE KC23A30.001SLS				
SCALE	DATE	DR	DWG	REV
1.5:1	6/28/2006	CT	G510274	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED