



- NOTE:
1. ALL DIMENSIONS IN MM[INCH].
  2. GENERAL TOLERANCE: X.X ± 0.4  
X.XX ± 0.25
  3. TERM. NOS. FOR REFERENCE ONLY.
  - ▲ 4. CONTACT MATERIAL: GOLD FLASH
  5. CONTACT RATING: 150mA, 250VAC/DC  
350mA, 110VAC/DC
  6. CONTACT RATING (NON-SWITCHING) 5A
  7. OPERATING FORCE 800± 300gf-cm
  8. OPERATING TEMP: -30°C to 85°C
  - ▲ 9. CIRCUIT DP: 6 POSITION 30° INDEX
  10. DIELECTRIC STRENGTH: 1000V RMS MIN.@ SEA LEVEL
  - ▲ 11. HARDWARE SUPPLIED ON SWITCH:  
STOP RING, LOCKWASHER, HEXNUT
  12. ▲ DENOTES CRITICAL PARAMETER.



A	22669	RELEASE FOR PRODUCTION	2/13/17	MW
REV	PCR NO	DESCRIPTION	DATE	BY
<small>THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED</small>				

<b>E-SWITCH®</b>				
TITLE KC26B30.002NLF				
SCALE	DATE	DR	DWG	REV
3:2	2/13/2017	MW	G510615	A