



- NOTE:
1. ALL DIMENSIONS IN MM[INCH].
 2. GENERAL TOLERANCE: X.X = ± 0.4
X.XX = ± 0.25
 3. TERM. NOS. FOR REFERENCE ONLY.
 - ▲ 4. CONTACT MATERIAL: GOLD OVER SILVER
 5. CONTACT RATING: 0.3A @ 125VAC
 6. OPERATING FORCE: 800 ± 300 gf-cm
 7. OPERATING TEMP: -30°C to 85°C
 - ▲ 8. CIRCUIT SP: 6 POSITION, SP, 60° INDEX
 9. DIELECTRIC STRENGTH: 500VAC FOR 1 MIN.
 - ▲ 10. HARDWARE SUPPLIED ON SWITCH: LOCKWASHER, HEXNUT
 11. ▲ DENOTES CRITICAL PARAMETER.



A	23834	RELEASED FOR PRODUCTION	4/9/19	MW
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE	KC60A10.001NPF			
SCALE	3:2	DATE	4/9/2019	DR
				MW
DWG	G510617	REV	A	

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED