



- NOTE:
1. ALL DIMENSIONS IN MM[INCH].
 2. GENERAL TOLERANCE: X.X ± 0.4
X.XX ± 0.25
 3. TERM. NUMBERS FOR REFERENCE ONLY.
 - ▲ 4. CONTACT MATERIAL: SILVER PLATED
 5. CONTACT RATING: 150mA, 250VAC/DC
350mA, 110VAC/DC
 6. CONTACT RATING (NON-SWITCHING) 5A
 7. OPERATING FORCE 800 ± 300 g-cm
 8. OPERATING TEMP: -30°C to 85°C
 - ▲ 9. CIRCUIT SP: 7 POSITION 30° INDEX
 10. DIELECTRIC STRENGTH: 1000V RMS MIN.@ SEA LEVEL
 - ▲ 11. HARDWARE SUPPLIED ON SWITCH:
LOCKWASHER, HEXNUT, STOP RING
 12. ▲ DENOTES CRITICAL PARAMETER



B	24826	redrawn, corrected bushing ht. to 8.0	3/30/21	MW
A	12633	RELEASED FOR PRODUCTION	12/5/02	CJB
REV	PCR NO	DESCRIPTION	DATE	BY

E-SWITCH®				
TITLE KC17A7.001NLS				
SCALE	DATE	DR	DWG	REV
3:2	12/5/2002	CJB	G527676	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED