



Key Pull: Pos. 3
 CIRCUIT: SP (45° INDEXING)
 CONTACT CONFIGURATION

SWITCH FUNCTION		
CONNECTED TERMINAL #		
POS. 1	POS. 2	POS. 3
8-1	1-2	2-3

RECOMMEND PANEL LAYOUT

- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: 0.0=±0.4
0.00=±0.25
 3. TERM. NOS. FOR REF. ONLY
 4. CONTACT RATING: 4A @125VAC/28VDC, 2A @250VAC
 5. CONTACT RESISTANCE: 10 milliohms Typical
 6. DIELECTRIC STRENGTH: 1kV RMS min. at sea level
 7. ELECTRICAL LIFE: 10,000 make-and-break cycles at full load.
 8. KEYS: Nickel plated with code no. A126 (2 Keys)
 9. ELECTROSTATIC DISCHARGE (ESD) RESISTANCE: 15KV DC min. @SEA LEVEL; Bushing to terminals



REV.	ECN No.	DESCRIPTION	DATE	CHKD
A	10566	RELEASED FOR PRODUCTION	3/13/00	MM

TITLE		SCALE		DATE		DR		DWG		REV	
KD130C-ESD Blk. Anti-Static (Key Code No. A126)		1.5:1		3/13/00		MM		K200254		A	

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED