



NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
3. TERM. NOS. FOR REFERENCE ONLY.
4. RATING: 4A @125VAC, 2A @250VAC
5. CONTACT RESISTANCE: 10mILLI-OHMS
6. DIELECTRIC STRENGTH: 1500 VAC-1Minute
7. INSULATION RESISTANCE: 200 Mega-OHMS
8. MATERIALS:

HOUSING: ZINC ALLOY DIE CAST  
 CYLINDER: ZINC ALLOY W/CHROME PLATE  
 TERMINAL AND CONTACTS: SILVER PLATE  
 CRISS CROSS TUMBLERS. (11 BLADE)  
 DOUBLE BITTED BRASS KEYS (2) STAMPED 2001

CIRCUIT: SPST (90° INDEXING)  
 CONTACT CONFIGURATION

SWITCH FUNCTION	
POS 1	POS 2
↑	→
OFF	ON

LEGEND

- = DETENT POSITIONS NO KEY PULL
- ⊙ = INDICATES KEY PULL POSSIBLE

RECOMMENDED PANEL CUTOUT

C	13648	TERMINALS BACK TO A VERSION	12/11/03	AR
B	13615	CORRECT TERMINALS	11/19/03	AR
A	11754	RELEASED FOR PRODUCTION	10/23/02	CJB
REV.	ECN No.	DESCRIPTION	DATE	CHKD

THE INFORMATION CONTAINED IN THIS DOCUMENT  
 IS PROPRIETARY TO E-SWITCH AND IS  
 NOT TO BE COPIED OR TRANSFERRED

<b>E-SWITCH®</b>				
TITLE K0128(SP)-2001				
SCALE 1.5:1	DATE 10/23/02	DR CJB	DWG K200407	REV C