



| PANEL THICKNESS | X dimension |
|-----------------------|-----------------|
| 0.75-1.25 [.030-.049] | 19.2-0.1 [.756] |
| 1.25-2.0 [.049-.079] | 19.4-0.1 [.764] |
| 2.0-3.0 [.079-.118] | 19.8-0.1 [.780] |



PANEL CUTOUT
NOT TO SCALE

| SWITCH FUNCTION | |
|-----------------|--------|
| POS. 1 | POS. 2 |
| ON | OFF |
| 1-1a | OPEN |



NOTES:

- ALL DIMENSIONS IN MM [INCH]
- GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
- TERMINAL NUMBERS FOR REF ONLY
- RATING: 15A @ 125VAC OR
6A @ 250VAC
- MATERIALS: TERMINALS: Silver Plated Copper Alloy
CONTACTS: Coin Silver, Silver Plated
- ELECTRIC LIFE: 10,000 cycles
- CONTACT RESISTANCE: <20 Mega Ω
- INSULATION RESISTANCE: >1000 Mega Ω
- DIELECTRIC STRENGTH: >1500 V 1 minute
>3000 V between poles

E-SWITCH®

| | | | | | |
|-------|--------|-------------------|---------|-----|--|
| TITLE | | R1966A BLK RED FF | | | |
| SCALE | DATE | DR | DWG | REV | |
| 1.5:1 | 7/3/00 | GLG | M309202 | B | |

| | | | | |
|--|---------|-------------|---------|------|
| B | 11664 | REVISED | 9/18/01 | CJB |
| REV. | ECN No. | DESCRIPTION | DATE | CHKD |
| THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED | | | | |