



- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NOS. FOR REFERENCE ONLY.
 4. RATING: 12VDC, 50mA
 - ▲5. OPERATING FORCE: 250 ± 50 gf
 6. TRAVEL: 0.25mm +0.20/-0.10MM
 7. CONTACT RESISTANCE: 100 MILLI OHMS MAX. (INITIAL)
 8. MECHANICAL/ELECTRICAL LIFE 100,000 CYCLES MIN.
 - ▲9. CONTACT MATERIAL: SILVER
 10. ▲ DENOTES CRITICAL PARAMETER
 11. OPERATING TEMP: -40°C TO 85°C



D	24544	CHANGED OPERATING TEMPERATURE	10/19/20	JM
C	10682	REVISED AND REDRAWN	6/4/2000	MM
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE TL1105AF250Q				
SCALE	DATE	DR	DWG	REV
4:1	8/14/1996	MM	P010012	D

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED