


ACTUATOR SPRING LOCATION TO IDENTIFY TERMINAL NUMBER



OBSOLETE
AUGUST 2015
PCR 21968

NOTES:

1. ALL DIMENSIONS IN INCHES [MILLIMETERS]
2. GENERAL TOLERANCE: .xxx = ±0.4
x.xx = ±.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 0.1A; 30V
5. CONTACT RESISTANCE: 50 MILLI-OHMS MAX. INITIAL
6. TIMING: NON-SHORTING
- ▲ 7. TRAVEL: FULL 1.8mm
8. OPERATING FORCE: 150 ± 50gf
9. ELECTRICAL LIFE: 10,000 CYCLES MAKE AND BREAK CYCLES AT FULL LOAD
10. ▲ DENOTE CRITICAL PARAMETER
11. 2002/95/EC (ROHS) COMPLIANT



| | | | | |
|----------------|-----------------|-------|-------------|-------|
| TITLE TL2203OA | | | | |
| SCALE 4 | DATE 12/17/2012 | DR rc | DWG P010407 | REV A |

| | | | | |
|--|--------|-------------|----------|----|
| A | 20934 | New Release | 12/19/12 | rc |
| REV | PCR NO | DESCRIPTION | DATE | BY |
| THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED | | | | |