



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X = ±0.4
X.XX = ±0.25
 3. CONTACT RATING: 12VDC, 50mA
 4. CONTACT RESISTANCE: 100 mΩ MAX.
 5. INSULATION RESISTANCE: 1MΩ MIN @ 100VDC.
 - ▲ 6. OPERATING FORCE: 260 ± 70gf
 7. TRAVEL: 0.3 +0.2/-0.1mm
 8. OPERATING TEMPERATURE: -40°C to +90°C
 9. STORAGE TEMPERATURE: -40°C to +90°C
 10. OPERATING LIFE: 10,000,000 CYCLES
 11. ▲ DENOTES CRITICAL PARAMETERS
 12. 2011/65/EU (ROHS) COMPLIANT
 13. PART IS IP67 RATED
 14. PARTS TO BE PACKAGED 500 PARTS PER BAG.



A	23759	New Release	1/30/2019	rc
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE TL6300AF260QP				
SCALE	DATE	DR	DWG	REV
4:1	1/21/2019	rc	P010696	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED