


RECOMMEND P.C.B. LAYOUT

OBSOLETE
 February 2017
 PCR 22710



CIRCUIT: SPDT

CONTACT CONFIGURATION

| SWITCH FUNCTION | | |
|-----------------|--------|--------|
| POS. 1 | POS. 2 | POS. 3 |
| <DN> | OFF | <DN> |
| 2-3 | OPEN | 2-1 |

< >=Momentary

NOTES:

1. ALL DIMENSIONS IN MM
2. TERM. NOS. FOR REF ONLY
3. RATING: 0.4VA Max. @20V Max. (AC or DC)

| | | | | | | | | | | | |
|--|-------------------------|------|------|------------------|--|-----------------------|--|-----|--|---------|--|
| | | | | E-SWITCH® | | | | | | | |
| | | | | TITLE | | 300A WSP-4 J3 VS3 R E | | | | | |
| A | RELEASED FOR PRODUCTION | | | SCALE | | DATE | | DR | | DWG | |
| REV. | DESCRIPTION | DATE | CHKD | 2:1 | | 9/21/98 | | MM | | T301404 | |
| THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED | | | | TOLERANCES | | 0.0 | | 0.0 | | REV | |
| | | | | ±0.4 | | ±0.25 | | MM | | A | |