




ISOMETRIC

SWITCH FUNCTION		
POS. 1	POS. 2	POS. 3
ON	OFF	ON
2-1,5-4	OPEN	2-3,5-6



NOTE:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
3. TERMINAL NUMBERS FOR REF ONLY
- ▲4. PLATING MATERIAL: SILVER
5. RATING: 1A @ 250VAC or 30VDC  
3A @ 120VAC OR 28VDC
6. ELECTRIC LIFE: 20,000 ACTUATIONS  
AT FULL LOAD.
7. INSULATION RESISTANCE: 1,000 MEGA-OHM MIN.
8. DIELECTRIC STRENGTH: 1,000 V RMS @SEA LEVEL.
9. OPERATING TEMP.: -40°C to 80°C
10. ▲ DENOTES CRITICAL PARAMETER.
11. 2002/95/EC (ROHS) COMPLIANT



E	20454	REMOVE (E) FROM DRAWING TITLE	2/7/12	BGL
D	17715	CHANGED TERMINAL LENGTH TO 3.94	9/25/07	BF
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE 600DP3S3M2Q				
SCALE 2:1	DATE 9/25/2007	DR BF	DWG T620306	REV E

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED