



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: x.x=± 0.4mm
x.xx=± 0.25mm
 3. RATING: DC 30V, 0.3A
 4. OPERATING FORCE: 200± 100gf
 5. TRAVEL: 3.3mm FULL TRAVEL
2.5mm TO LOCK
 6. LIFE CYCLES: 10,000 CYCLES
 7. OPERATING TEMPERATURE: -20°C TO 70°C
 8. CONTACT RESISTANCE: 20mΩ MAX.
 9. INSULATION RESISTANCE: 100MΩ MIN@ 500VDC.
 - ▲10. LED COLOR: BICOLOR GREEN-BLUE
 11. ▲ DENOTES CRITICAL PARAMETER.
 12. 2002/95/EC (RoHS) COMPLIANT.

R05 BUTTON TRANSPARENT (B410000)

▲ WBL4UEERQ (B400013)

LED SPECS	UNITS	GREEN	BLUE
FORWARD CURRENT	mA	20	20
FORWARD VOLTAGE @20mA	V	2.1 TYP-2.5 MAX	3.2 TYP - 4.0 MAX
LUMINOUS INTENSITY @ 20mA	mcd	160 TYP	160 TYP



B	21534	CORRECT PCB LAYOUT, UPDATE DRAWING	8/4/14	EBP
A	20705	New-Release	8/13/12	rc
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE WBL4UEEGBQR05CLR				
SCALE	DATE 8/13/2012	DR RC	DWG XB0941P	REV B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED