



- NOTES:
1. ALL DIMENSIONS IN MM [INCH].
 2. GENERAL TOLERANCE: x.x = ± 0.4
x.xx = ± 0.25
 3. TERM. NOS. FOR REF. ONLY.
 4. RATING: 5A @250VAC
8A @125VAC
.2A @250VDC
6A @24VDC
 5. INSULATION: 1,000 MΩ MIN.
 6. DIELECTRIC STRENGTH: 2000V FOR 1 MIN.
 7. SEALED TO IP65.
 8. TRAVEL: 3.0mm
 9. ELECTRICAL LIFE: >50,000 CYCLES
 10. OPERATING TEMP: -25C to +55C
 11. PANEL THICKNESS: 0.5mm to 3.0mm
 12. LAMP VOLTAGE: LED, 6VDC GREEN
 13. ▲ DENOTES CRITICAL PARAMETER

▲ Parts List			
ITEM	QTY	PART NUMBER	DESCRIPTION
1	1		LASOAU32 BODY
2	1	F051706	35MM FLUSH MOUNT BEZEL
3	1	F051707	35MM FLUSH MOUNT RETAINER
4	1	F060212	29MM GREEN LENS
5	1	F050416	LED 6VDC GREEN



A	23780	RELEASED FOR PRODUCTION	2/22/19	MW
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE LASOAU32HGRNGRN				
SCALE 1	DATE 2/22/2019	DR MW	DWG XF0921P	REV A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED