



- NOTE:
- ALL DIMENSIONS IN MM [INCH]
  - GENERAL TOLERANCE: X.X = ± 0.4  
X.XX = ± 0.25
  - TERMINAL NUMBERS FOR REF. ONLY
  - RATING: 2A @ 48VDC
  - CONTACT RESISTANCE: 50mΩ MAX. @ 1A 12VDC
  - INSULATION RESISTANCE: 1,000MΩ @ 500VDC
  - DIELECTRIC STRENGTH: 2,000VAC MIN. FOR 1 MINUTE
  - ELECTRICAL LIFE: 50,000 CYCLES
  - OPERATING TEMPERATURE: -20°C to 55°C
  - INGRESS PROTECTION: IP66
  - ▲ DENOTES CRITICAL PARAMETER
  - SUPPLIED HARDWARE: O-RING AND HEXNUT
  - ILLUMINATION COLOR: RED (FORWARD), BLUE (REVERSE)
  - ILLUMINATION VOLTAGE: 6V



B	24637	UPDATE THREAD LENGTH TO 15.0	12/10/20	JM
A	24366	Release	6/26/20	MW
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE PV9F2V0SS-3H3				
SCALE 1:1	DATE 6/26/2020	DR MW	DWG 52-PV9F2V0SS3H3	REV B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED