



- NOTE:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X = ± 0.4
X.XX = ± 0.25
 3. TERM NOS. FOR REFERENCE ONLY.
 - ▲ 4. CONTACT RATING: 5A @ 250VAC - UL, VDE
8A @ 125VAC - UL, CSA
6A @ 24VDC - UL, CSA
 5. CONTACT RESISTANCE: 100mΩ MAX. (TYPICAL)
 6. INSULATION RESISTANCE: 1000MΩ
 7. ACTUATION FORCE: 300g/POLE
 8. OPERATING TEMPERATURE: -20°C TO 55°C
 9. CONTACT MATERIAL: SILVER PLATED COPPER ALLOY
 - ▲ 10. TRAVEL: 3.0mm
 11. ▲ DENOTES CRITICAL PARAMETER
 12. 2002/95/EC (ROHS) COMPLIANT



C	19729	UPDATE DRAWING	3/3/11	BGL
REV	PCR NO	DESCRIPTION	DATE	BY

E-SWITCH				
TITLE D16OAS21				
SCALE	DATE	DR	DWG	REV
1.5:1	3/2/2011	BGL	F040033	C

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED