



- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NOS. FOR REFERENCE ONLY.
 - ▲ 4. RATING: 50VDC, 50mA
 5. OPERATING FORCE: 500±100 gms
 6. TRAVEL: 0.25mm +0.2/-0.1
 7. CONTACT RESISTANCE: 100 MILLI OHMS MAX. (INITIAL)
 - ▲ 8. SILVER CONTACTS
 - ▲ 9. PACKAGE: 750 PCS PER TAPE AND REEL
 10. ▲ DENOTES CRITICAL PARAMETER
 11. 2002/95/EC (ROHS) COMPLIANT
 12. LIFE: 100,00 CYCLES

E-SWITCH®

TITLE TL3301TF500QG

A	15961	RELEASED FOR PRODUCTION	4/13/06	CT
REV	PCR NO	DESCRIPTION	DATE	BY

SCALE	DATE	DR	DWG	REV
4:1	4/13/2006	CT	P010626	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED