


RECOMMENDED MOUNTING PAD
SCALE: 4:1



NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4 X:XX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 50mA, @12VDC
5. DOME: STAINLESS STEEL
6. OPERATING FORCE: 160 ±50gf
7. TRAVEL: 0.25 +0.2/-0.1mm
8. CONTACT RESISTANCE: 100 ohms max.
9. PACKAGED: TAPE & REEL QTY 1100
10. 2002/95/EC (ROHS) COMPLIANT
11. MECHANICAL LIFE: 1,000,000
12. CONTACT MATERIAL: SILVER
13. ▲ DENOTES CRITICAL PARAMETER



TL3301AF1600JSSDDME

B	16690	UPDATED NOTES	11/22/06	TN
A	16507	RELEASED FOR PRODUCTION	11/3/06	TN
REV.	ECN No.	DESCRIPTION	DATE	CHKD

TITLE		SCALE	DATE	DR	DWG	REV
TL3301AF1600JSSDDME		3:1	11/22/2006	TN	P010641	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED