



- NOTES:
1. ALL DIMENSIONS IN MM
  2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
  3. TERM. NOS. FOR REFERENCE ONLY.
  4. RATING: 50VDC, 50mA
  - ▲ 5. OPERATING FORCE: 160 ± 50 gms
  6. TRAVEL: 0.25mm +0.2/-0.1MM
  7. CONTACT RESISTANCE: 100 MILLI OHMS MAX. (INITIAL)
  8. MECHANICAL/ELECTRICAL LIFE 100,000 CYCLES MIN.
  - ▲ 9. CONTACTS: GOLD
  10. PACKAGED TAPE AND REEL - 750 PIECES PER REEL. (D)
  11. 2002/95/EC (ROHS) COMPLIANT
  12. ▲ DENOTES CRITICAL PARAMETER

**E-SWITCH®**

D	20967	750 WAS 1000	1/14/13	EBP
C	20800	Redrawn	10/01/12	RC
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE TL3301TF160RG				
SCALE	DATE	DR	DWG	REV
4:1	10/1/2012	rc	P010792	D

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED