


O.P. (MM)	F.P. (MM)
14.8±0.8	16.0 MAX

O.P. = OPERATING POINT
F.P. = FREE-POSITION



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X±0.4
X.XX±0.25
 3. RATING: .1A @125VAC; 2A @ 12VDC;
0.5A @ 42VDC; 1A @ 24VDC;
UL, CUL APPROVED
 - ▲ 4. OPERATING FORCE: 70 GRAMS MAX.
 5. OPERATING TEMP: -25°C to 85°C
 6. ELECTRICAL LIFE: 10,000 CYCLES MIN.
 7. MECHANICAL LIFE: 1,000,000 CYCLES TYP.
 8. INSULATION RESISTANCE: >100 MEGA-OHMS @ 500VDC
 9. DIELECTRIC STRENGTH: 600VAC
 10. CONTACT RESISTANCE: 100 MILLI-OHMS MAX (INITIAL).
 11. 2011/65/EC (ROHS) COMPLIANT.
 12. ▲ DENOTES CRITICAL PARAMETER.



REV	PCR NO	DESCRIPTION	DATE	BY
B	23345	update Terminal callout	5/3/18	MW
A	23213	New Release	2/12/18	rc

E-SWITCH®				
TITLE WS0850102F070SA				
SCALE	DATE	DR	DWG	REV
2:1	2/12/2018	rc	Q930008	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED