



CONTACT CONFIGURATION

CIRCUIT: SPST

OFF ON

() = Momentary

- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: 0.0=±0.4
0.00=±0.25
 3. TERM. NOS. FOR REF. ONLY
 4. CONTACT RATING: 0.4 VA max. @20 VAC or DC max.
 5. FIXED TERMINAL & MOVING CONTACT: Cu alloy w/Au plate over Ni plate.
 6. ELECTRICAL LIFE: 50,000 make-and-break cycle at full load.
 7. DIELECTRIC STRENGTH: 1,000 V RMS @sea level.
 8. OPERATING TEMP.: -30°C to 85°C

E-SWITCH®

C	11200	ADD DIMENSION	1/26/01	CJB
B	11073	PLUNGER: 2.79 WAS 10.11	11/29/00	PML
REV.	ECN NO.	DESCRIPTION	DATE	CHKD

TITLE		SCALE	DATE	DR	DWG	REV
800B WSP-9 SM6 R E W/ .110" PLUNGER		2:1	11/28/00	PML	T833019	C

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED