




2.30
[.091 in]



NOTES:

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. RATING: 50mA @ 12VDC
4. TRAVEL: 0.25 +0.2/0.1mm
- ▲5. OPERATING FORCE: 160±50gf
6. CONTACT RESISTANCE: 100 Milli-Ohms Max
7. 2002/95/EC (ROHS) COMPLIANT
- ▲8. SHORTER LEAD WITH COLOR IS NEGATIVE (CATHODE).
9. ▲ DENOTES CRITICAL PARAMETER

LED SPECS	UNITS	YELLOW
FORWARD CURRENT	mA	20
FORWARD VOLTAGE	V	2.1-2.6
LUMINOUS INTENSITY	MCD	45



TITLE		TL1240YQ2JRED	
SCALE	4:1	DATE	12/28/2010
DR	BGL	DWG	XP0194P
REV		REV	C

REV	PCR NO	DESCRIPTION	DATE	BY
C	19550	DRAWING UPDATE / CLEAN-UP	12/28/10	BGL

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED